


8 x 19S + FC / 8 x 19W + FC / 8 x 25F + FC / 8 x 26WS + FC


Käyttökohteet: Nosturit, siltanosturit, nostimet, paalutuskoneet.

Vähimmäismurtokuormituskerroin: 0.293


Massakerroin: 0.340




8x19S+FC



8x19W+FC



8x25F+FC



8x26WS+FC

Halkaisija mm	Paino 100 m kg	Vähimmäismurtokuorma 1,770 N/mm ²		Vähimmäismurtokuorma 1,960 N/mm ²	
		kN	kg	kN	kg
8	21,80	33,20	3 390	36,80	3 750
9	27,50	42,00	4 280	46,50	4 740
10	34,00	51,90	5 290	57,40	5 850
11	41,10	62,80	6 410	69,50	7 090
12	49,00	74,70	7 600	82,70	8 430
13	57,50	87,60	8 900	97,10	9 900
14	66,60	102,00	10 400	113,00	11 500
16	87,00	133,00	13 600	147,00	14 500
18	110,00	168,00	17 100	186,00	19 000
20	136,00	207,00	21 100	230,00	23 500
22	165,00	251,00	25 600	278,00	28 400
24	196,00	299,00	30 500	331,00	33 800
26	230,00	351,00	35 800	388,00	39 600
28	267,00	407,00	41 500	450,00	45 900
32	348,00	531,00	54 200	588,00	60 000
36	441,00	672,00	68 500	744,00	75 900




8 x 19S + IWRC / 8 x 19W + IWRC /
8 x 25F + IWRC / 8 x 26WS + IWRC


Käyttökohteet: Nosturit, siltanosturit, nostimet, paalutuskoneet.

Vähimmäismurtokuormituskerroin: 0.356


Massakerroin: 0.407




8x19S+IWRC



8x19W+IWRC



8x25F+IWRC



8x26WS+IWRC

Halkaisija mm	Paino 100 m kg	Vähimmäismurtokuorma 1,770 N/mm ²		Vähimmäismurtokuorma 1,960 N/mm ²	
		kN	kg	kN	kg
8	26,00	40,30	4 110	44,70	4 560
9	33,00	51,00	5 200	56,50	5 760
10	40,70	63,00	6 430	69,80	7 120
11	49,20	76,20	7 770	84,40	8 610
12	58,60	90,70	9 250	100,00	10 200
13	68,80	106,00	10 800	118,00	12 000
14	79,80	124,00	12 600	137,00	13 400
16	104,00	161,00	16 400	179,00	18 300
18	132,00	204,00	20 800	226,00	23 000
20	163,00	252,00	25 700	279,00	28 500
22	197,00	305,00	31 100	338,00	34 500
24	234,00	363,00	37 000	402,00	41 000
26	275,00	426,00	43 400	472,00	48 100
28	319,00	494,00	50 400	547,00	55 800
32	417,00	645,00	65 800	715,00	72 900

