

KEVENTIMET ENDO



Malli	Työalue (kg) Min. ~ Max.	Vaijerin pituus (m)	Vaijerin halkaisija (mm)	Korkeus (mm)	Paino (kg)
EK-0	0,5 ~ 1,5	1	3	237	0,5
EWS-3	1,5 ~ 3,0	1,3	3	290	1,9
EWS-5	3,0 ~ 5,0	1,3	3	290	2,1
EWS-7	5,0 ~ 7,0	1,3	3	290	2,1
EWF-9	4,5 ~ 9,0	1,3	4	340	3,4
EWF-15	9,0 ~ 15,0	1,3	4	340	3,8
EWF-22	15,0 ~ 22,0	1,5	4,76	445	7,2
EWF-30	22,0 ~ 30,0	1,5	4,76	445	7,6
EWF-40	30,0 ~ 40,0	1,5	4,76	445	9,8
EWF-50	40,0 ~ 50,0	1,5	4,76	445	10,4
EWF-60	50,0 ~ 60,0	1,5	4,76	445	11,6
EWF-70	60,0 ~ 70,0	1,5	4,76	445	11,8
EWF-90	70,0 ~ 90,0	2,0	4,76	499	22,0
EWF-105	85,0 ~ 105,0	2,0	4,76	499	24,0
EWF-120	100,0 ~ 120,0	2,0	4,76	499	28,0